



GRAFFITI SHIELD

Gloss finish

Anti Graffiti Coating



Graffiti shield is a non sacrificial anti graffiti coating. It's a clear acrylic coating that can be applied to masonry and painted surfaces, timber, tiles, terrazzo and metal. The products UV and chemical resistant properties means that it will last up to 10 years before re application may be required. The gloss appearance of the treated surface can act as a deterrent for graffiti artists. To remove any graffiti from a treated surface, depending on the graffiti paint type, use water, methyated spirits or mineral turpentine.

DIRECTIONS FOR USE:

Ensure the substrate to be coated is clean and dry before application.

Apply Graffiti Shield by use of a paint roller, paint brush or low pressure air assisted spray apparatus.

Two coats wet on wet is recommended for most applications, however three or four coats can be applied where extreme protection is required.

Coating is fully cured after 24 hours.

Washup using Mineral Turpentine or suitable solvent. Coverage approximately 5m² per litre per coat

FIRST AID: Inhalation: Move subject to fresh air apply artificial respiration if necessary. Eyes: Flush with copious amounts of water and lift eye lids occasionally, seek medical advise. Skin: Thoroughly wash exposed area with soap and water Indigestion: Do NOT induce vomiting. Drink plenty of water and seek medical advise

Rapelle Pty Ltd

1/7 Jubilee Ave Warriewood NSW 2102

p. +612 9979 8860 f. +612 9999 2086

www.rapelle.com.au ABN: 44 059 750 882

